

Serial No. 09/476,461

AMENDMENTS TO THE CLAIMS

1. (Currently Amended) A method for use in a mobility gateway for forwarding a call directed to a roaming subscriber unit, the method comprising:

storing in memory, at the mobility gateway coupled between a GSM network and an ANSI-41 based network, a plurality of temporary transfer-to telephone numbers;
[and]

selecting, for association with the roaming subscriber unit, one of the temporary transfer-to telephone numbers||.||;

sending a message having the temporary transfer-to telephone number to a mobile switching center serving the roaming subscriber unit;

after selecting and sending, receiving and storing information related to a call request for the roaming subscriber unit; and

receiving a location request message from a mobile switching center.

2. (Original) The method according to claim 1, wherein the temporary transfer-to telephone number is homed on a mobile switching center that is different from a mobile switching center serving the roaming subscriber unit.

3. (Canceled)

4. (Canceled)

5. (Currently Amended) The method according to claim [[4]] 1, further comprising:

Serial No. 09/476,461

associating the location request message with the call request for the roaming subscriber unit.

6. (Currently Amended) The method according to claim [[4]] 1, further comprising:
associating the location request message with the call request for the roaming subscriber unit based at least in part on the temporary transfer-to telephone number.
7. (Original) The method according to claim 5, further comprising:
after associating, sending a redirection request message to a gateway mobile switching center which received the call request.
8. (Currently Amended) A mobility gateway for use in connection between an ANSI-41-based network and a GSM-based network, the mobility gateway comprising:
a processor;
memory for storing a plurality of temporary transfer-to telephone numbers homed on one or more mobile switching centers (MSCs) that is different from a mobile switching center serving a roaming subscriber unit;
said processor being operative for:
selecting one of the plurality of temporary transfer-to telephone numbers for association with the roaming subscriber unit [[.]];
sending a message having the temporary transfer-to telephone number to a GSM MSC serving the roaming subscriber unit;
after selecting and sending, receiving and storing information related to a call request for the roaming subscriber unit; and
receiving a location request message from an MSC.
9. (Original) The mobility gateway according to claim 8, wherein the selected temporary transfer-to telephone number associated with the roaming subscriber unit is homed on an ANSI-41 MSC different from a GSM MSC serving the roaming subscriber unit.
10. (Canceled)

Serial No. 09/476,461

11. (Canceled)
12. (Currently Amended) The mobility gateway according to claim [[11]] 8, wherein said processor is further operative for:
 - associating the location request message with the call request for the roaming subscriber unit.
13. (Currently Amended) The mobility gateway according to claim [[11]] 8, wherein said processor is further operative for:
 - associating the location request message with the call request for the roaming subscriber unit based at least in part on the temporary transfer-to telephone number.
14. (Original) The mobility gateway according to claim 12, wherein said processor is further operative for:
 - after associating, sending a redirection request message to an ANSI gateway MSC which received the call request.
15. (Previously Amended) A method for use in forwarding a call between an ANSI-41 based network and a GSM-based network intended for a subscriber unit, comprising:
 - receiving and storing information related to a call request for a roaming subscriber unit;
 - after receiving and storing, receiving a location request message from a mobile switching center which homes a temporary transfer-to telephone number associated with the roaming subscriber unit;
 - after receiving a location request message from a mobile switching center, correlating the message with a previous request message received by a mobility gateway;
 - associating the location request message with the call request for the roaming subscriber unit; and
 - after associating, sending a redirection request message to a gateway mobile switching center which received the call request for the roaming subscriber unit.

Serial No. 09/476,461

16. (Original) The method according to claim 15, further comprising, prior to receiving and storing the information related to the call request:
- selecting the temporary transfer-to telephone number for association with a roaming subscriber unit; and
 - sending a message having the temporary transfer-to telephone number to a mobile switching center serving the roaming subscriber unit.
17. (Original) The method according to claim 15, further comprising:
- wherein the receiving and storing of information related to the call request includes receiving and storing information comprising subscriber identification information and call identification information; and
 - wherein sending the redirection request message includes sending the call identification information.
18. (Original) The method according to claim 15, further comprising:
- wherein receiving the location request message comprises receiving the temporary transfer-to telephone number; and
 - wherein associating the location request message with the call request comprises associating based on the temporary transfer-to telephone number.
19. (Currently Amended) A method for use in a mobility gateway coupled between an ANSI-41 based network and a GSM-based network, comprising:
- selecting a temporary transfer-to telephone number for association with a roaming subscriber unit;
 - sending a message having the temporary transfer-to telephone number to a mobile switching center serving the roaming subscriber unit;
 - after selecting and sending, receiving and storing information related to a call request for the roaming subscriber unit;
 - after receiving and storing, receiving a location request message from a mobile switching center which homes the temporary transfer-to telephone number;

Serial No. 09/476,461

after receiving a location request message from a mobile switching center, correlating the message with a previous request message received by a mobility gateway;

associating the location request message with the call request for the roaming subscriber unit; and

after associating, sending a redirection request message to a gateway mobile switching center which received the call request for the roaming subscriber unit.

20. (Original) The method according to claim 19, further comprising:

wherein the receiving and storing of information related to the call request includes receiving and storing information comprising subscriber identification information and call identification information; and

wherein sending the redirection request message includes sending the call identification information.

21. (Original) The method according to claim 19, wherein the mobile switching center serving the roaming subscriber unit comprises a GSM mobile switching center and the gateway mobile switching center comprises an ANSI gateway mobile switching center.